

TRW TOP COTE DRY TEXTURE

Bag Size:	20kg bags
Grades:	Medium or Fine
Coverage:	7 – 10 m ²
Suitable over:	TRW Base Renders
Apply With:	Trowel



Product Description:

TRW Top Cote Dry Texture finishes are dry powder-based products. They are a modified cement-based blend of fine marble, quality-graded mineral and polymeric additives to provide a 100% active product. On-site, all that has to be added is water to provide a ready-to-apply finish.

TRW Top Cote Dry Texture finishes are polymer/mineral bound textured coatings designed for decorating interior and exterior walls. TRW Dry Texture Finishes are suitable for use over surfaces prepared with Render from the TRW Base Render range. Dry Texture is a one-coat application that offers a long-life, heavy-duty coating and contains quality graded fine mineral components and aggregates, together with non-absorbent extenders bound by a well-proven polymer system, providing biological resistance from bacteria and fungi.

TRW Top Cote Dry Texture finishes are not pigmented products and dry on the surface to a 'cement-off-white' colour. The desired topcoat colour is achieved by application of a pigmented protective membrane.

Application Details:

A minimum of 72 hours, under ideal temperate conditions, is required to through dry (and cure) of the render, when the surface is trough dry the TRW Top Cote Dry Texture Render coat may be applied.

The substrate must be clean and dry cured before applying the Finish coat. Any crumbling, loose or damaged substrate render must be removed and the surface patched and made good prior to coating. All surfaces must be free of grease, oils, dirt and dust. Pre-painted surfaces must have flaking paint wire brushed back to a sound substrate. TRW Top Cote Dry Texture, when dry and cured, is to be over coated with TRW Membrane.

Application should not be carried out under excessively cold conditions (below 7°C) or in hot windy conditions (above 32°C).



Guide to Good Mixing Consistency

Add the contents of the bag slowly to 4 litres of water (25% volume of entire bag) with vigorous drill mixing to ensure a lump free render of required slump. The mix can be later water thinned to required viscosity. Ensure wall surface is stable, clean, dry and free of dust etc., prior to application.

Material Safety Data (MSD)

Product Name: TRW Top Cote Dry Texture

Use: External and Internal Render

Specific Gravity: Average S.G. approximately 1.85

Health Hazard Data

TRW Top Cote Dry Texture Render contains cement and care must be taken to avoid excessive amounts of dust. Short-term exposure can irritate skin, eyes and mucous membranes. Wet cement, especially as an ingredient in unhardened concrete is slightly caustic and long-term exposure can dry the skin and cause alkali burns. There may also be trace amounts of water-soluble hexavalent chromium in cement, which may cause allergic dermatitis in some individuals.

First Aid: Skin: Wash with tepid soapy water

Eyes: Flush with cool water for at least 10 minutes and seek medical attention

Swallowed: Wash mouth and lips with water and seek medical attention

Inhaled: Move to fresh air, wash with water and seek medical attention if effects persist

Precautions of use

Ventilation: Where Practical, suitable means of dust collection/suppression should be applied

Personal Protection: In dusty environments, the use of filter masks as in AS1716 (class A) and tightly fitting goggles is advised. Barrier creams or impervious gloves, boots and clothing to protect the skin from contact with dust and wet cement are recommended.

Flammability: TRW Top Cote Dry Texture Render is non-combustible.

Spills and Disposal: Spillages should be cleaned up with a broom, shovel or suitable vacuum by suitably attired personnel.

Contact: TRW on 1800render or (03) 9540 0963